

# CPD® CHLORINATED RUBBER CURE & SEAL

## DESCRIPTION

CPD® Chlorinated Rubber Cure & Seal is a rapid drying chlorinated rubber based sealer designed to cure, seal and dustproof interior concrete floors and slabs. When applied to freshly placed and finished concrete surfaces, it prevents rapid evaporation of the gauging water, providing an efficient and economical method of curing concrete.

## WHERE TO USE

- \$ to cure, seal and dustproof interior concrete floors and slabs
- \$ colored version is used to cure & seal colored concrete flooring

## BENEFITS

- \$ seals out construction stains and reduces the cost of cleaning up after work is completed
- \$ retards surface evaporation of gauging water thereby insuring proper curing of new concrete floors

## APPLICATION

Apply by roller or low pressure hand or power spray evenly to concrete surfaces approximately 1-2 hours after completion of finishing operations and/or immediately after disappearance of surface moisture. Under normal conditions, surface coating will be dry in approximately 2 hours. A second coat should be applied only after an overnight drying period of the first coat. Provide ventilation in work area during and after application.

## LIMITATIONS

- \$ CPD® Chlorinated Rubber Cure & Seal yellows slightly and should not be used on white cement concrete, exposed aggregate or wherever yellowing will be objectionable. CPD® Acrylic Cure & Seal may be used where a non-yellowing sealer is desired
- \$ do not use CPD® Chlorinated Rubber Cure & Seal for exterior applications
- \$ food stuffs such as meats, vegetables and dairy products, etc. may pick up odors when this product is drying
- \$ designed as an initial curing and sealing treatment only; not as a long lasting traffic bearing coating

- \$ Wood or tile flooring with an adhesive should not be applied over concrete floors cured with CPD® Chlorinated Rubber Cure & Seal unless the flooring manufacturer supplies a type of adhesive that is compatible with CPD® Chlorinated Rubber Cure & Seal.

## COVERAGE

New Concrete: 1<sup>st</sup> Coat – 4.8m<sup>2</sup>/L (200ft<sup>2</sup>/U.S. Gal)  
2<sup>nd</sup> Coat – 8m<sup>2</sup>/L (326ft<sup>2</sup>/U.S. Gal)

## STANDARDS

Manufactured to comply with ASTM C-309, Type 1; (Clear and ASTM C-309 Type II (Colored))

## COLORS AVAILABLE

Clear, French Grey, Tile Red

## PACKAGING

208 L (55 U.S. gal) drums - 204 kg (450 lb)/drum  
18.9L (5 U.S. gal) pail - 19 kg (42 lb)/pail  
3.79 L (1 U.S. gal) can - 4 kg (8.8 lb)/can

## CLEAN UP

Clean all equipment and tools with Xylene solvent.

## STORAGE

Contains flammable solvents. Keep away from open flame. Keep containers tightly closed when not in use.

## SHELF LIFE

Two years from date of manufacture when stored in original unopened container, and under normal warehouse conditions.

## SAFETY PRECAUTION

Flammable Liquid. Consult Material Safety Data Sheet (M.S.D.S.) for specific instructions. MSDS # 33 (Clear), MSDS #33A (Colored).

## **WARRANTY**

The recommendations made and the information herein is based on our own and independent laboratory experience, and is believed to be accurate under controlled conditions. However, no warranty or guarantee of accuracy is made because we cannot cover every possible application of product nor anticipate every variation encountered in weather conditions, job-conditions, methods used and types of surfaces on which the product is applied. The users shall make their own tests to determine the suitability of such products for any particular purpose.

CPD® makes no warranties with respect to this product, expressed or implied, without limitation, the implied warranties of merchantability or fitness for a particular purpose.

CPD®'s liability shall be limited in all events to supplying sufficient product to re-treat and/or repair the specific area to which CPD® product has been applied. CPD® reserves the right to have the true cause of any difficulty determined by accepted test methods. CPD® shall have no other liability, including liability for incidental, consequential or resultant damages, however caused, whether due to breach of warranty, negligence, or strict liability.

**THIS WARRANTY MAY NOT BE MODIFIED OR EXTENDED BY REPRESENTATIVES OF CPD®, ITS DISTRIBUTORS OR DEALERS.**