

CPD[®] CLEAR & GREEN CURE (SOLVENT BASE)

DESCRIPTION

CPD[®] Clear & Green Cure (Solvent Base) is a membrane type curing compound that is composed of selected hydrocarbon resins blended in a solvent base. The membrane prevents water loss, retaining 95% or more of the water in concrete for 7 days. The membrane is designed to eventually flake off once the curing function has been completed. CPD[®] Green Cure has a fugitive green dye which insures uniform coverage through visual observation. Fugitive dye disappears after approximately 72 hours exposure to sunlight.

WHERE TO USE

CPD[®] Clear & Green Cure (Solvent Base) can be used on concrete floors, sidewalks, pavements, driveways and runways.

BENEFITS

- \$ high moisture retention for optimum cure
- \$ available in clear and green
- \$ interior and exterior applications
- \$ help control dusting

APPLICATION

The optimum time for application is approximately 1-2 hours after final surface finishing and after surface moisture has disappeared. Apply as evenly as possible using brush or low pressure hand or power spray. Avoid gaps, puddles or pinholes. Similar to paint, there may be some separation or settlement of solids on storage. A short period of stirring or agitation will restore uniformity prior to use. Provide ventilation in work areas during and after application if used indoors.

LIMITATIONS

CPD[®] Clear & Green Cure (Solvent Base) is not recommended for:

- \$ application as a chemically resistant coating
- \$ hardening of carbonated concrete surfaces
- \$ areas where solvent exposure is a service condition
- \$ surfaces that will subsequently be coated with paint or adhesives

COVERAGE

Coverage is approximately 4.6m²/L (190 ft²/U.S. gallon) depending on surface porosity. Dries in about 4 hours under normal temperature conditions 20°C (68°F).

STANDARDS

Manufactured to comply with ASTM C-309, Type 1 and CRD-C-300.

Approved for use on all MTQ (Ministry of Transportation) projects.

PACKAGING

208L (55 U.S. gal) drums - 195 kg (429 lbs.)/drum
18.9L (5 U.S. gal) pail - 18 kg (40 lbs.)/pail

CLEAN UP

Clean all equipment and tools with water directly after use.

STORAGE

Contains flammable solvents. Keep away from open flame. Keep containers tightly closed when not in use. Provide ventilation in work areas during and after application if used indoors.

SHELF LIFE

Two years from date of manufacture when stored in original unopened container, and under normal warehouse conditions.

SAFETY PRECAUTION

Flammable Liquid. Consult Material Safety Data Sheet (M.S.D.S.) for specific instructions. MSDS # 30 and 30A.

WARRANTY

The recommendations made and the information herein is based on our own and independent laboratory experience, and is believed to be accurate under controlled conditions. However, no warranty or guarantee of accuracy is made because we cannot cover every possible application of product nor anticipate every variation encountered in weather conditions, job-conditions, methods used and types of surfaces on which the product is applied. The users shall make their own tests to determine the suitability of such products for any particular purpose.

CPD® makes no warranties with respect to this product, expressed or implied, without limitation, the implied warranties of merchantability or fitness for a particular purpose.

CPD®'s liability shall be limited in all events to supplying sufficient product to re-treat and/or repair the specific area to which CPD® product has been applied. CPD® reserves the right to have the true cause of any difficulty determined by accepted test methods. CPD® shall have no other liability, including liability for incidental, consequential or resultant damages, however caused, whether due to breach of warranty, negligence, or strict liability.

THIS WARRANTY MAY NOT BE MODIFIED OR
EXTENDED BY REPRESENTATIVES OF CPD®,
ITS DISTRIBUTORS OR DEALERS.