

CPD[®] COLORED MASONRY AND CONCRETE SEALER

DESCRIPTION

CPD[®] Colored Masonry and Concrete Sealer is a color pigmented, modified acrylate with a solvent base.

WHERE TO USE

- \$ seal new concrete after full cure
- \$ dustproof and seal existing concrete
- \$ seal block and masonry walls

BENEFITS

- \$ one component, ready-to-use
- \$ quality adhesives for vinyl, rubber and other types of resilient flooring are compatible with CPD[®] Colored Concrete and Masonry Sealer (Test to verify compatibility)
- \$ resistant to most oils, greases and detergents

APPLICATION

Surface must be clean and free of oil, grease, dirt, curing compounds and other foreign matter. If doubt exists as to the condition of the surface, chemical cleaning may be required. New concrete surfaces must be dry before applying sealer.

Stir material prior to application until a uniform color is evident. Do not thin. Apply by brush, roller or low pressure hand or power spray. Do not puddle. Allow 24 hours drying time between coats. Allow a minimum of 48 hours after application of final coat prior to resumption of traffic.

Provide ventilation in work areas during and after application.

LIMITATIONS

- \$ food stuffs such as meats, vegetables and dairy products etc. may pick up odors when this product is drying
- \$ not recommended as a chemically resistant coating
- \$ not recommended where solvent exposure is a service condition

COVERAGE

Approximately 6-8m²/L (250 - 350ft² per U.S. gal) per coat.

COLORS AVAILABLE

French Grey and Tile Red

PACKAGING

18.9L (5 U.S. gal) pail - 19 kg (42 lb)/pail
3.79L (1 U.S. gal) pail - 4/carton - 16 kg (35.3 lb)/carton

CLEAN UP

Clean all equipment and tools with xylene.

STORAGE

Contains flammable solvents. Keep away from open flame. Keep containers tightly closed when not in use.

SHELF LIFE

Two years from date of manufacture when stored in original unopened container, and under normal warehouse conditions.

SAFETY PRECAUTION

Flammable Liquid. Consult Material Safety Data Sheet (M.S.D.S.) for specific instructions. MSDS # 61.

WARRANTY

The recommendations made and the information herein is based on our own and independent laboratory experience, and are believed to be accurate under controlled conditions. However, no warranty or guarantee of accuracy is made because we cannot cover every possible application of product nor anticipate every variation encountered in weather conditions, job-conditions, methods used and types of surfaces on which the product is applied. The users shall make their own tests to determine the suitability of such products for any particular purpose.

CPD[®] makes no warranties with respect to this product, expressed or implied, without limitation, the implied warranties of merchantability or fitness for a particular purpose.

CPD[®]'s liability shall be limited in all events to supplying sufficient product to re-treat and/or repair the specific area to which CPD[®] product has been applied.

CPD[®] reserves the right to have the true cause of any difficulty determined by accepted test methods. CPD[®] shall have not other liability, including liability for incidental, consequential or resultant damages, however caused, whether due to breach of warranty, negligence, or strict liability.

THIS WARRANTY MAY NOT BE MODIFIED OR EXTENDED BY REPRESENTATIVES OF CPD[®], ITS DISTRIBUTORS OR DEALERS.