

# CPD<sup>®</sup> HARD-CURE



## DESCRIPTION

CPD<sup>®</sup> Hard-Cure is a surface hardening compound supplied in a ready to use form. CPD<sup>®</sup> Hard-Cure is used to harden and dust proof concrete floors.

## WHERE TO USE

\$ hardening and dustproofing existing concrete floors  
\$ suitable for concrete floors in warehouses, industrial plants, commercial and residential buildings

## BENEFITS

\$ water based - no fumes or fire hazard  
\$ economical solution to dustproofing and hardening concrete floors  
\$ imparts a semi-gloss finish to concrete floors

## APPLICATION

### Cured Concrete (for surface hardening/dustproofing):

Clean floor thoroughly using an alkaline concrete detergent only. DO NOT ACID WASH. Rinse with water and allow to dry thoroughly. Apply the CPD Hardcure as supplied by roller, push broom or spray. Avoid leaving puddles. Allow to dry overnight then thoroughly wash with clean water. Allow to thoroughly dry then re-apply as per first coat. Once again, wash with clean water once floor has dried. A third application may be required for some floors. NOTE: When using CPD<sup>®</sup> Hard-Cure on concrete, the concrete must be thoroughly cured (28 days minimum).

## LIMITATIONS

\$ do not apply on glass, brick or aluminum surfaces  
\$ not recommended for carbonated concrete (very old floors should be tested for this condition before treating).

## COVERAGE

\$ Cured Concrete - 5 m<sup>2</sup>/L (200 ft<sup>2</sup>/U.S. gallon) for the first coat. Higher coverage for the following coats depending on density of the concrete floor.

## PACKAGING

208L (55 U.S. gal) drum - 250 kg (550 lbs.)  
18.9L (5 U.S. gal) pail - 23 kg (50 lbs.)  
3.79L (1 U.S. gal) pail - 18 kg (40 lbs.)/case (4 per case)

## CLEAN UP

Clean all tools and equipment immediately after using with clean water.

## STORAGE

Protect from freezing.

## SHELF LIFE

Two years stored under normal heated warehouse conditions in original unopened containers.

## SAFETY PRECAUTIONS

Consult Material Safety Data Sheet (M.S.D.S.) for specific instructions. M.S.D.S. # 57.

## WARRANTY

The recommendations made and the information herein is based on our own and independent laboratory experience, and is believed to be accurate under controlled conditions.

However, no warranty or guarantee of accuracy is made because we cannot cover every possible application of product nor anticipate every variation encountered in weather conditions, job conditions, methods used and types of surfaces on which the product is applied. The users shall make their own tests to determine the suitability of such products for any particular use.

CPD<sup>®</sup> makes no warranties with respect to this product, expressed or implied, without limitation, the implied warranties of merchantability or fitness for a particular purpose.

CPD<sup>®</sup>'s liability shall be limited in all events to supplying sufficient product to re-treat and/or repair the specific area to which CPD<sup>®</sup> product has been applied. CPD<sup>®</sup> reserves the right to have the true cause of any difficulty determined by accepted test methods. CPD<sup>®</sup> shall have no other liability for incidental, consequential or resultant damages, however caused, whether due to breach of warranty, negligence, or strict liability.

THIS WARRANTY MAY NOT BE MODIFIED OR EXTENDED BY REPRESENTATIVES OF CPD<sup>®</sup>, ITS DISTRIBUTORS OR DEALERS.

03390-20-0908