

## CPD<sup>®</sup> P-6842 Primer

### DESCRIPTION

CPD<sup>®</sup> P-6842 Primer is a liquid bonding agent for use with CPD<sup>®</sup> Topcrete SL.

### WHERE TO USE

Used as a bonding agent, CPD<sup>®</sup> P-6842 permits direct application of CPD<sup>®</sup> Topcrete SL to structurally sound surfaces.

### BENEFITS

- \$ bond is stronger than most concrete
- \$ low viscosity to penetrate and seal surface
- \$ prevents air voids from forming in CPD<sup>®</sup> Topcrete SL

### PROPERTIES

Type: vinyl acetate polymer. Not affected by alkalinity of lime or Portland cement.

### APPLICATION

Surface must be structurally sound, free of dirt, grease, oil, etc. After diluting CPD<sup>®</sup> P-6842 with water and mixing completely, it should be broomed into the surface to be topped. Broom out puddles. The primer should be completely dry before the topping is applied. In any case it should be kept free of all traffic and topped within 24 hours.

### LIMITATIONS

- \$ protect from freezing
- \$ do not apply when temperature is below 7°C (45°F)
- \$ do not use as a bonding agent in areas subject to constant water exposure or immersion

### COVERAGE

CPD<sup>®</sup> P-6842 is mixed with water at a ratio of 1 part CPD<sup>®</sup> P-6842 to 2 parts potable water (by volume). 3.8L (1 U.S. gallon) of diluted CPD P-6842 will cover approximately 9.29-11.6 m<sup>2</sup> (100-125 ft<sup>2</sup>). For porous concrete it may be necessary to apply a second coat.

### PACKAGING

- 18.9L (5 U.S. gal) - 23 kg (51 lb)
- 3.79L (1 U.S. gal) - 4.3 kg (9.5 lb)
- 1L (0.26 U.S. gal) - 1.2 kg (2.6 lb)

### STORAGE

Do not freeze. Store in a heated warehouse above 4.5°C (40°F).

### SHELF LIFE

One year from date of manufacture when stored in original unopened container, and under normal warehouse conditions.

### SAFETY PRECAUTION

Consult Material Safety Data Sheet (M.S.D.S.) for specific instructions. MSDS # 206.

### WARRANTY

The recommendations made and the information herein is based on our own and independent laboratory experience, and is believed to be accurate under controlled conditions. However, no warranty or guarantee of accuracy is made because we cannot cover every possible application of product nor anticipate every variation encountered in weather conditions, job-conditions, methods used and types of surfaces on which the product is applied. The users shall make their own tests to determine the suitability of such products for any particular purpose.

CPD<sup>®</sup> makes no warranties with respect to this product, expressed or implied, without limitation, the implied warranties of merchantability or fitness for a particular purpose.

CPD<sup>®</sup>'s liability shall be limited in all events to supplying sufficient product to re-treat and/or repair the specific area to which CPD<sup>®</sup> product has been applied. CPD<sup>®</sup> reserves the right to have the true cause of any difficulty determined by accepted test methods. CPD<sup>®</sup> shall have no other liability, including liability for incidental, consequential or resultant damages, however caused, whether due to breach of warranty, negligence, or strict liability.

THIS WARRANTY MAY NOT BE MODIFIED OR EXTENDED BY REPRESENTATIVES OF CPD<sup>®</sup>, ITS DISTRIBUTORS OR DEALERS.