

CPD[®] TRAPROCK #8 & #9

DESCRIPTION

CPD[®] Traprock #8 & #9 is a factory blend of non-metallic floor hardener. This hardener provides a high strength, hard wearing surface for industrial and commercial applications.

WHERE TO USE

Applications include processing plants, water and recycling plants, warehouses, distribution facilities and suitable in areas exposed to abrasive and light to medium traffic.

BENEFITS

- high strength
- good abrasive resistance
- good resistance to impact and loading
- non-rusting

PROPERTIES

Composition.....	fine grained Basalt-Volcanic Origin (Traprock)
Compressive Strength.....	193MPa (28,000 psi) (Pure Hardener)
Hardness.....	7 Moh Scale
Specific Gravity.....	2.96
Absorption.....	0.00%

TRAPROCK #9

<u>Size</u>	<u>% Retained</u>
#40	6.2%
#30	17.8%
#20	28.9%
#16	40.6%
#12	5.1%
#6	0.6%

TRAPROCK #8

<u>Size</u>	<u>% Retained</u>
#20	18.5%
#12	77.2%
#6	2.9%

The above information is representative of actual production runs. Independent test results may vary from the above by approximately ± 10%.

PACKAGING

Traprock #8	20 Kg. (44lbs)
Traprock #9	20 Kg. (44lbs)

STORAGE

May be stored anywhere under a tarp on pallets as long as the product is kept dry.

SAFETY PRECAUTIONS

Consult Material Safety Data Sheet (M.S.D.S.) for specific instructions. MSDS #76

WARRANTY

The recommendations made and the information herein is based on our own and independent laboratory experience, and is believed to be accurate under controlled conditions. However, no warranty or guarantee of accuracy is made because we cannot cover every possible application of product nor anticipate every variation encountered in weather conditions, job-conditions, methods used and types of surfaces on which the product is applied. The users shall make their own tests to determine the suitability of such products for any particular purpose.

CPD[®] makes no warranties with respect to this product, expressed or implied, without limitation, the implied warranties of merchantability or fitness for a particular purpose.

CPD[®]'s liability shall be limited in all events to supplying sufficient product to re-treat and/or repair the specific area to which CPD[®] product has been applied. CPD[®] reserves the right to have the true cause of any difficulty determined by accepted test methods. CPD[®] shall have no other liability, including liability for incidental, consequential or resultant damages, however caused, whether due to breach of warranty, negligence, or strict liability.

THIS WARRANTY MAY NOT BE MODIFIED OR EXTENDED BY REPRESENTATIVES OF CPD[®], ITS DISTRIBUTORS OR DEALERS.