

CPD® ODORLESS CHEMICAL FORM RELEASE AGENT

DESCRIPTION

CPD® Odorless Chemical Form Release Agent is premium multiple release agent with no odor.

WHERE TO USE

Suitable for use on steel forms in pipe casting and precast plants, plywood, timber and plastic faced forms and molds.

BENEFITS

- \$ ready-to-use (do not dilute)
- \$ will not discolor or stain concrete
- \$ odorless
- \$ very effective on steel forms

APPLICATION

Forms must be clean, dry and free from cement residue, rust, scale, etc. Brush or spray on a thin coating avoiding excessive build-up, runs or puddles as this may surface retard the concrete. Initially apply before the first casting and thereafter re-apply as required.

Note: New timber and plywood may completely absorb the first coat requiring a second application.

LIMITATIONS

- \$ not for lift or tilt-up construction
- \$ not recommended for use in autolaves

COVERAGE

Coverage rate may vary depending on the texture and absorption rate of the forms:

Wood, plywood forms 17-24m²/L (700-1000 ft²/U.S.gal) Plastic and metal forms 27-29m²/L (1000-1200 ft²/U.S. gal)

PACKAGING

208L (55 U.S. gal) drums - 194 kg (428 lbs.)/drum
18.9L (5 U.S. gal) pails - 18 kg (40 lbs.)/pail

CLEAN UP

Clean spray equipment, brushes, etc with mineral spirits.

STORAGE

Store under heated warehouse conditions where possible. Avoid all contamination with water (for exterior storage store on side only). Sub-zero storage (0°C/32°F) not recommended.

SHELF LIFE

Two years from the date of manufacture in original containers providing product has not been contaminated with water.

SAFETY PRECAUTIONS

Combustible Liquid. Controlled product under WHMIS regulations. Consult Material Safety Data Sheet (M.S.D.S.) for specific instructions. MSDS # 15.

WARRANTY

The recommendations made and the information herein is based on our own and independent laboratory experience, and is believed to be accurate under controlled conditions. However, no warranty or guarantee of accuracy is made because we cannot cover every possible application of product nor anticipate every variation encountered in weather conditions, job-conditions, methods used, and types of surfaces on which the product is applied. The users shall make their own tests to determine the suitability of such products for any particular purpose.

CPD® makes no warranties with respect to this product, expressed or implied, without limitation, the implied warranties of merchantability or fitness for a particular purpose.

CPD®'s liability shall be limited in all events to supplying sufficient product to re-treat and/or repair the specific area to which CPD® product has been applied. CPD® reserves the right to have the true cause of any difficulty determined by accepted test methods. CPD® shall have no other liability, including liability for incidental, consequential or resultant damages, however caused, whether due to breach of warranty, negligence, or strict liability.

THIS WARRANTY MAY NOT BE MODIFIED OR EXTENDED BY REPRESENTATIVES OF CPD®, ITS DISTRIBUTORS OR DEALERS.