

	SAFET	Y DATA SHEET	Page 1		
		IDENTIFICATION	1 490 1		
PRODUCT NAME: CPD FASTCRETE ULTRA PART "A" POWDER					
MANUFACTURER/SUPPLIER:	219 Conr	CPD Construction Products 219 Connie Crescent, Unit #13 Concord, Ontario Canada L4K 1L4			
24 HOUR EMERGENCY NUMBER:	CANUTI	CANUTEC: (613) 996-6666			
PRODUCT DESCRIPTION:	Patching	compound. This is a two-component p STCRETE ULTRA PART "B" LATE.	product. The other component is		
SECTI	ON 2: HAZA	ARDS INDENTIFICATION			
GHS CLASSIFICATION	(Category (Category	ation (Category 2); Serious eye damag / 1A-Inhalation); Specific target organ / 3- Respiratory system); Specific targ exposure (Category 1-Lungs)	systemic toxicity-single exposure		
	\rangle				
SIGNAL WORD		R			
HAZARD STATEMENTS		uses skin irritation.			
		ises serious eye damage.			
		y cause respiratory irritation. y cause cancer by inhalation.			
		ses damage to organs (Lungs) throug	h prolonged or repeated exposure		
PRECAUTIONARY STATEMENTS	11372 Cu	uses duringe to organs (Durigs) throug	in protonged of repeated exposure.		
PREVENTION	P202 Do	not handle until all safety precautions	have been read and understood.		
P260 Do not breath dust.					
P264 Wash skin thoroughly after handling.					
	P270 Do not eat, drink or smoke when using this product.				
P271 Use only outdoors or in a well-ventilated area.					
P280 Wear protective gloves/ eye protection/face protection. P281 Use personal protective equipment as required.					
RESPONSE		52 IF ON SKIN: wash with plenty of s			
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for					
breathing.					
		51+P338 IF IN EYES: Rinse cautious			
	Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/ attention.				
		nediately call a POISON CENTER/ do			
		13 If skin irritation occurs: Get medica			
	P362 Tak	e off contaminated clothing and wash	before reuse.		
SECTION 3 : COI	MPOSITION	/INFORMATION ON INGRED	IENTS		
Hazardous Ingredients %	C.AS. #	LD/50, Route, Species	LC/50, Route, Species		
Silica Sand ** (Quartz) 30-60	4808-60-7	>5,000mg/kg (Oral-Rat)	Not Available		
Portland Cement (Hydraulic Cement) 30-60 6	5997-15-1	Not Available	Not Available		
**The sand used in this product contains approximately 85% (by weight) Quartz. The Quartz that exists as dust particles, with aerodynamic diameter less than 5 microns, is hazardous. An approved dust mask (for crystalline silica) should be worn by workers handling this product in the dry state.					



	SAFETY DATA SHEET Page 2			
SECTI	ON 4 : FIRST-AID MEASURES			
FIRST-AID MEASURES				
EYE CONTACT	Flush eyes with lukewarm water for at least 15 minutes holding eye lids open.			
SKIN CONTACT	If irritation persists see a physician. Wash with soap and water and remove contaminated clothing. Wash clothing separately prior to reuse. If irritation persists, get medical attention.			
INHALATION INGESTION	Remove victim to fresh air. Consult a physician after significant exposure. If swallowed, DO NOT induce vomiting. Rinse mouth and call a physician or poison control centre immediately. Never give anything by mouth to an			
	unconscious person. Obtain medical attention.			
SYMPTOMS AND EFFECTS EYE CONTACT	Mild imitation and discound at more successive lashermation as evidences			
	Mild irritation and discomfort, may cause excessive lachrymation or serious eye damage.			
SKIN CONTACT	Irritation may occur. Prolonged or repeated contact may result in skin sensitization and dermatitis.			
INHALATION	Prolonged inhalation may result in respiratory irritation, coughing. May cause cancer by inhalation.			
CHRONIC	May cause damage to organs through prolonged or repeated exposure.			
	5: FIRE-FIGHTING MEASURES			
FLAMMABILITY CLASSIFICATION SENSITIVITY OF STATIC DISCHARGE	Not flammable or combustible. Not applicable.			
SUITABLE EXTINGUISHING MEDIA	This product will not burn. Use the medium appropriate to the surrounding fire.			
SPECIAL FIRE FIGHTING PROCEDURES	Wear self-contained breathing apparatus and protective clothing if necessary Use self-contained breathing apparatus and protective clothing for large fires.			
HAZARDOUS COMBUSTION PRODUCTS	None.			
SECTION 6: A	ACCIDENTAL RELEASE MEASURES			
PERSONAL PRECAUTIONS	Use personal protective equipment. Avoid dust formation. Avoid breathing dust. Ensure adequate ventilation.			
ENVIRONMENTAL PRECAUTIONS	Do not let product enter drains. Do not flush into surface water or sanitary sewer system.			
CLEAN-UP METHODS	Pick-up and arrange disposal without creating dust. Sweep up and shovel using dust retarding floor sweeping compound. Keep in closed containers for disposal.			
SECTION 7: HANDLING AND STORAGE				
HANDLING PROCEDURES	Avoid contact with skin and eyes. Avoid formation of dust and dust inhalation. Provide appropriate exhaust ventilation in places where dust is formed			
STORAGE NEEDS	Store in original labelled container, tightly closed and in a dry, well-ventilated place.			
SECTION 8: EXPOSU	JRE CONTROLS / PERSONAL PROTECTION			
EXPOSURE LIMITS (respirable fraction in air):				
SILICA SAND (QUARTZ)	OSHA & MSHA-PEL 10 mg/m ³ (8 hour TWA) ACGIH-TLV 0.05 mg/m ³ (8 hour TWA)			
PORTLAND CEMENT	NIOSH 0.05 mg/m ³ (10 hour TWA, 40 h work week) OSHA- PEL, ACGIH-TLV, NIOSH 5 mg/m ³ (TWA)			
PROTECTIVE EQUIPMENT:				
EYE / TYPE	Safety eyewear should be used when a risk assessment indicates as necessary. Avoid breathing dust. For operations where inhalation exposure can occur, a			
	NIOSH approved respirator may be necessary.			
SKIN/ BODY PROTECTION OTHER / TYPE	Wear protective clothes; long sleeves and trousers to prevent dermal exposure. Eyewash fountain. Emergency shower should be in close proximity.			
VENTILATION REQUIREMENTS	General dilution and local exhaust as necessary to control airborne dusts below appropriate airborne concentration standards/guidelines.			
	appropriate an oorne concentration standards/guidelines.			



	SAFETY DATA SHEET Page 3				
SECTION 9: PH	YSICAL AND CHEMICAL PROPERTIES				
PHYSICAL STATE	Powder/Granular Solid				
VAPOUR PRESSURE	Not applicable				
VISCOSITY	Not applicable				
VAPOUR DENSITY (AIR=1)	Not applicable				
SPECIFIC GRAVITY @20°C (68°F)	2.2				
BOILING POINT	Not applicable				
SOLUBILITY IN WATER	2.0%				
APPEARANCE	Dark to Light Grey Powder containing fine Silica Sand				
ODOUR	None				
pH LEVEL	12.0 @ 20°C (68°F) (Aqueous Solution)				
% VOLATILE	Not applicable				
EVAPORATION RATE (N-BuAc=1)	Not applicable				
SECTION 10: STABILITY AND REACTIVITY					
CHEMICAL STABILITY	Product is stable.				
POSSIBLE HAZARDOUS REACTIONS	Hazardous polymerization will not occur under normal storage conditions.				
CONDITIONS TO AVOID	Do not allow the product to get wet as it will harden. Store in a dry place.				
INCOMPATIBLE MATERIALS	No data available.				
HAZARDOUS DECOMPOSITION PRODUCTS:	Product is stable, hazardous decomposition will not occur.				
SECTION 11	: TOXICOLOGICAL INFORMATION				
INGREDIENTS LD50/ LC50 DATA	Refer to Section 3.				
ROUTES OF EXPOSURE:					
EYE CONTACT	Irritating.				
SKIN CONTACT	Frequent or prolonged contact may irritate the skin, low toxicity.				
INHALATION (ACUTE)	Prolonged or repeated exposure may cause allergic reactions in certain sensitive individuals. Respirable Silica Quartz can cause chronic silicosis.				
CARCINOGENICITY OF MATERIAL	May cause cancer by inhalation. The Silica Quartz component is classified as carcinogenic to humans by NTP and IARC-Group 1.				
TERATOGENICITY	No data available.				
MUTAGENICITY	No data available.				
REPRODUCTIVE EFFECTS	No data available.				
OTHER	The dust product may be harmful if inhaled. Causes respiratory tract irritation. Prolonged exposure can cause silicosis. May be harmful if swallowed. Causes				
	skin and eye irritation.				
SIGNS AND SYMPTOMS OF EXPOSURE	Coughing, skin rash, allergic dermatitis.				
SECTION 12: ECOLOGICAL INFORMATION					
ECOTOXICITY	No data available.				
PERSISTENCE AND DEGRADABILITY	No data available.				
BIOACCUMULATIVE POTENTIAL	No data available.				
MOBILITY IN THE SOIL	No data available.				
OTHER EFFECTS	No data available.				
SECTION 13: DISPOSAL CONSIDERATIONS					
PRODUCT DISPOSAL	Disposal of this product should comply with the requirements of environmental				
	protection and waste disposal legislation in place.				
	Do not allow product to enter sewers, streams or lakes.				
WASTE DISPOSAL	Empty containers of this product can be disposed of as normal garbage.				
SECTION 14: TRANSPORTATION INFORMATION					
TDG CLASSIFICATION	Not regulated.				



	SAFETY DATA SHEET	Page 4			
SECTION 15: REGULATORY INFORMATION					
WHMIS CLASSIFICATION	Class E (Portland Cement) Class D Division 2 Subdivision A (Silica Quartz)				
CPR (CANADA) COMPLIANCE	Meets all requirements				
SECTION 16: OTHER INFORMATION					
ACGIH IARC	American Confederation of Governmental Industrial Hygienists International Agency for Research on Cancer National Toxicology Program Short Term Exposure Limit Permissible Exposure Limit Threshold Limit Value - Time-Weighted Average Occupational Safety and Health Administration National Institute for Occupational Safety and Health Mine Safety and Health Administration Controlled Products Regulations Chemical Abstracts Service Personal Protection Equipment Not available				
PREPARED BY: TELEPHONE NUMBER: PREPARATION DATE:	Camelia Gardo (905) 669-5013 October 8 th , 2017				

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.