

SAFETY DATA SHEET	Page 1
SECTION 1: IDENTIFICATION	
PRODUCT NAME: CPD RAPIDCRETE	

MANUFACTURER/SUPPLIER: CPD Construction Products 219 Connie Crescent, Unit #13

Concord, Ontario Canada L4K 1L4

24 HOUR EMERGENCY NUMBER: CANUTEC: (613) 996-6666

APPLICATION AND USE: A Non-Shrink Patching Compound for use in repair of concrete floors. Also used

for grouting base plates, anchor bolts and posts.

PRODUCT DESCRIPTION: Fast setting Portland Cement Patching Compound

SECTION 2: HAZARDS INDENTIFICATION

repeated exposure (Category 1-Lungs)







SIGNAL WORD	DANGER
HAZARD STATEMENTS	H315 Causes skin irritation.
	H318 Causes serious eye damage.
	H335 May cause respiratory irritation.
	H350 May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS

P260 Do not breath dust.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/face protection.

P281 Use personal protective equipment as required.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/ attention.

P310 Immediately call a POISON CENTER/doctor.

P332+P313 If skin irritation occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

SECTION COMMODITION ON MINISTER OF MINISTER OF STREET				
Hazardous Ingredients	%	C.AS. #	LD/50, Route, Species	LC/50, Route, Species
Silica Sand ** (Quartz)	30-60	14808-60-7	>5,000 mg/Kg (Oral-Rat)	Not Available
Portland Cement (Hydraulic Cement)	30-60	65997-15-1	Not Available	Not Available

(Hydraulic Cement) 30-60 65997-15-1 Not Available Not Available **The sand used in this product contains approximately 85% (by weight) Quartz. The Quartz that exists as dust particles, with

aerodynamic diameter less than 5 microns, is hazardous. An approved dust mask (for crystalline silica) should be worn by workers handling this product in the dry state.



	SAFETY DATA SHEET Page 2			
SECTI	ON 4 : FIRST-AID MEASURES			
FIRST-AID MEASURES				
EYE CONTACT	Flush eyes with lukewarm water for at least 15 minutes holding eye lids open. If irritation persists see a physician.			
SKIN CONTACT	Wash with soap and water and remove contaminated clothing. Wash clothing separately prior to reuse. If irritation persists, get medical attention.			
INHALATIONINGESTION	Remove victim to fresh air. Consult a physician after significant exposure. If swallowed, DO NOT induce vomiting. Rinse mouth and call a physician or poison control centre immediately. Never give anything by mouth to an unconscious person. Obtain medical attention.			
SYMPTOMS AND EFFECTS	unconscious person. Obtain inculcar attention.			
EYE CONTACT	Mild irritation and discomfort, may cause excessive lachrymation or serious eye damage.			
SKIN CONTACT	Irritation may occur. Prolonged or repeated contact may result in skin sensitization and dermatitis.			
INHALATION	Prolonged inhalation may result in respiratory irritation, coughing. May cause cancer by inhalation.			
CHRONIC	May cause damage to organs through prolonged or repeated exposure.			
SECTION	N 5: FIRE-FIGHTING MEASURES			
FLAMMABILITY CLASSIFICATION	Not flammable or combustible. Not applicable. This product will not burn. Use the medium appropriate to the surrounding fire. Wear self-contained breathing apparatus and protective clothing if necessary Use self-contained breathing apparatus and protective clothing for large fires.			
HAZARDOUS COMBUSTION PRODUCTS				
SECTION 6: A	ACCIDENTAL RELEASE MEASURES			
PERSONAL PRECAUTIONS	Use personal protective equipment. Avoid dust formation. Avoid breathing dust. Ensure adequate ventilation.			
ENVIRONMENTAL PRECAUTIONS	Do not let product enter drains. Do not flush into surface water or sanitary sewer system.			
CLEAN-UP METHODS	Pick-up and arrange disposal without creating dust. Sweep up and shovel using dust retarding floor sweeping compound. Keep in closed containers for disposal.			
SECTIO	N 7: HANDLING AND STORAGE			
HANDLING PROCEDURES	Avoid contact with skin and eyes. Avoid formation of dust and dust inhalation.			
STORAGE NEEDS	Provide appropriate exhaust ventilation in places where dust is formed Store in original labelled container, tightly closed and in a dry, well-ventilated place.			
SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION				
EXPOSURE LIMITS (respirable fraction in air):				
SILICA SAND (QUARTZ)	OSHA & MSHA-PEL 10 mg/m³ (8 hour TWA) ACGIH-TLV 0.05 mg/m³ (8 hour TWA) NIOSH 0.05 mg/m³ (10 hour TWA, 40 h work week)			
PORTLAND CEMENT	OSHA- PEL, ACGIH-TLV, NIOSH 5 mg/m³ (TWA)			
PROTECTIVE EQUIPMENT:				
EYE / TYPE	Safety eyewear should be used when a risk assessment indicates as necessary. Avoid breathing dust. For operations where inhalation exposure can occur, a NIOSH approved respirator may be necessary.			
SKIN/ BODY PROTECTION	Wear protective clothes; long sleeves and trousers to prevent dermal exposure.			
OTHER / TYPE VENTILATION REQUIREMENTS	Eyewash fountain. Emergency shower should be in close proximity. General dilution and local exhaust as necessary to control airborne dusts below appropriate airborne concentration standards/guidelines.			



	SAFETY DATA SHEET Page 3				
SECTION 9: PH	YSICAL AND CHEMICAL PROPERTIES				
PHYSICAL STATE	Powder/Granular Solid				
VAPOUR PRESSURE	Not applicable				
VISCOSITY	Not applicable				
VAPOUR DENSITY (AIR=1)	Not applicable				
SPECIFIC GRAVITY @20°C (68°F)	3.00				
BOILING POINT	Not applicable				
SOLUBILITY IN WATER	<1.0%				
APPEARANCE	Light Grey Powder containing Fine Sand				
ODOUR	None				
pH LEVEL	12.5 @ 20°C (68°F) (Aqueous Solution)				
% VOLATILE	Not applicable				
EVAPORATION RATE (N-BuAc=1)	Not applicable				
SECTION	10: STABILITY AND REACTIVITY				
CHEMICAL STABILITY	Product is stable.				
POSSIBLE HAZARDOUS REACTIONS	Hazardous polymerization will not occur under normal storage conditions.				
CONDITIONS TO AVOID	Do not allow the product to get wet as it will harden. Store in a dry place.				
INCOMPATIBLE MATERIALS	No data available.				
HAZARDOUS DECOMPOSITION PRODUCTS:	Product is stable, hazardous decomposition will not occur.				
SECTION 11	: TOXICOLOGICAL INFORMATION				
INGREDIENTS LD50/ LC50 DATA	Refer to Page 1 Section 3				
ROUTES OF EXPOSURE:	1.0101 to 1.000 1.0001.01				
EYE CONTACT	Irritating.				
SKIN CONTACT	Frequent or prolonged contact may irritate the skin, low toxicity.				
INHALATION (ACUTE)	Prolonged or repeated exposure may cause allergic reactions in certain sensitive				
, , , , , , , , , , , , , , , , , , , ,	individuals. Respirable Silica Quartz can cause chronic silicosis.				
CARCINOGENICITY OF MATERIAL	May cause cancer by inhalation. The Silica Quartz component is classified as				
	carcinogenic to humans by NTP and IARC-Group 1.				
TERATOGENICITY	No data available				
MUTAGENICITY	No data available				
REPRODUCTIVE EFFECTS	No data available				
OTHER	The dust product may be harmful if inhaled. Causes respiratory tract irritation.				
	Prolonged exposure can cause silicosis. May be harmful if swallowed. Causes				
	skin and eye irritation.				
SIGNS AND SYMPTOMS OF EXPOSURE	Coughing, skin rash, allergic dermatitis.				
SECTION 12: ECOLOGICAL INFORMATION					
ECOTOXICITY	No data available.				
PERSISTENCE AND DEGRADABILITY	No data available				
BIOACCUMULATIVE POTENTIAL	No data available.				
MOBILITY IN THE SOIL	No data available.				
OTHER EFFECTS	No data available.				
SECTION 13: DISPOSAL CONSIDERATIONS					
PRODUCT DISPOSAL	Disposal of this product should comply with the requirements of environmental				
	protection and waste disposal legislation in place.				
	Do not allow product to enter sewers, streams or lakes.				
WASTE DISPOSAL	Empty containers of this product can be disposed of as normal garbage.				
SECTION 14: TRANSPORTATION INFORMATION					
TDG CLASSIFICATION	Not regulated.				



	SAFETY DATA SHEET	Page 4			
SECTION 15: REGULATORY INFORMATION					
WHMIS CLASSIFICATION CPR (CANADA) COMPLIANCE	Class E (Portland Cement) Class D Division 2 Subdivision A (Silica Quartz) Meets all requirements				
<u> </u>	<u> </u>				
SECT	ION 16: OTHER INFORMATION				
ACGIH IARC NTP STEL PEL TLV-TWA OSHA NIOSH MSHA CPR CAS PPE N/A	American Confederation of Governmental Industrial Hygienists International Agency for Research on Cancer National Toxicology Program Short Term Exposure Limit Permissible Exposure Limit Threshold Limit Value - Time-Weighted Average Occupational Safety and Health Administration National Institute for Occupational Safety and Health Mine Safety and Health Administration Controlled Products Regulations Chemical Abstracts Service Personal Protection Equipment Not available				
PREPARED BY: TELEPHONE NUMBER: PREPARATION DATE:	Camelia Gardo (905) 669-5013 October 8 th , 2017				

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.