

	SAFETY DATA SHEET	Page 1		
SECTION 1: IDENTIFICATION				
PRODUCT NAME: CPD SUPERPLUG				
MANUFACTURER/SUPPLIER:	219 Connie Crescent, Unit #13			
24 HOUR EMERGENCY NUMBER:	Concord, Ontario Canada L4K 1L4 CANUTEC: (613) 996-6666 Water plug and fast setting patching compound. Blend of Hydraulic Cements and Silica Aggregate.			

SECTION 2: HAZARDS INDENTIFICATION

GHS CLASSIFICATION Skin irritation (Category 2); Serious eye damage (Category 1); Carcinogenicity (Category 1A-Inhalation); Specific target organ systemic toxicity-single exposure

(Category 3- Respiratory system); Specific target organ systemic toxicity-

repeated exposure (Category 1-Lungs)







SIGNAL WORD	DANGER
HAZARD STATEMENTS	H315 Causes skin irritation.
	H318 Causes serious eye damage.
	H335 May cause respiratory irritation.
	H350 May cause cancer by inhalation.
	H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.
PRECAUTIONARY STATEMENTS	
PREVENTION	P202 Do not handle until all safety precautions have been read and understood.
	P260 Do not breath dust.
	P264 Wash skin thoroughly after handling.
	P270 Do not eat, drink or smoke when using this product.
	P271 Use only outdoors or in a well-ventilated area.
	P280 Wear protective gloves/ eye protection/face protection.
	P281 Use personal protective equipment as required.
RESPONSE	P302+P352 IF ON SKIN: wash with plenty of soap and water.
	P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for
	breathing.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.
	Remove contact lenses, if present and easy to do. Continue rinsing.
	P308+P313 IF exposed or concerned: Get medical advice/ attention.
	P310 Immediately call a POISON CENTER/ doctor.
	P332+P313 If skin irritation occurs: Get medical advice/ attention.
	P362 Take off contaminated clothing and wash before reuse.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS				
Hazardous Ingredients	%	C.AS. #	LD/50, Route, Species	LC/50, Route, Species
Silica Sand ** (Quartz)	30-60	14808-60-7	>5,000 mg/ Kg (Oral-Rat)	Not Available
Portland Cement (Hydraulic Cement)	30-60	65997-15-1	Not Available	Not Available
ababited 1 1 1 1 1 1		1 050/ (1	1100	

^{**}The sand used in this product contains approximately 85% (by weight) Quartz. The Quartz that exists as dust particles, with aerodynamic diameter less than 5 microns, is hazardous. An approved dust mask (for crystalline silica) should be worn by workers handling this product in the dry state.



	SAFETY DATA SHEET Page 2
SECTI	ION 4 : FIRST-AID MEASURES
FIRST-AID MEASURES	
EYE CONTACT	Flush eyes with lukewarm water for at least 15 minutes holding eye lids open. If irritation persists see a physician.
SKIN CONTACT	Wash with soap and water and remove contaminated clothing. Wash clothing separately prior to reuse. If irritation persists, get medical attention.
INHALATION	Remove victim to fresh air. Consult a physician after significant exposure. If swallowed, DO NOT induce vomiting. Rinse mouth and call a physician or poison control centre immediately. Never give anything by mouth to an unconscious person. Obtain medical attention.
SYMPTOMS AND EFFECTS	
EYE CONTACT	Mild irritation and discomfort, may cause excessive lachrymation or serious eye damage.
SKIN CONTACT	Irritation may occur. Prolonged or repeated contact may result in skin sensitization and dermatitis.
INHALATION	Prolonged inhalation may result in respiratory irritation, coughing. May cause cancer by inhalation.
CHRONIC	May cause damage to organs through prolonged or repeated exposure.
SECTION	N 5: FIRE-FIGHTING MEASURES
FLAMMABILITY CLASSIFICATION	Not flammable or combustible. Not applicable. This product will not burn. Use the medium appropriate to the surrounding fire. Wear self-contained breathing apparatus and protective clothing if necessary
HAZARDOUS COMBUSTION PRODUCTS	Use self-contained breathing apparatus and protective clothing for large fires. None.
SECTION 6: A	ACCIDENTAL RELEASE MEASURES
PERSONAL PRECAUTIONS	Use personal protective equipment. Avoid dust formation. Avoid breathing dust. Ensure adequate ventilation.
ENVIRONMENTAL PRECAUTIONS	Do not let product enter drains. Do not flush into surface water or sanitary sewer system.
CLEAN-UP METHODS	Pick-up and arrange disposal without creating dust. Sweep up and shovel using dust retarding floor sweeping compound. Keep in closed containers for disposal.
SECTIO	N 7: HANDLING AND STORAGE
HANDLING PROCEDURES	Avoid contact with skin and eyes. Avoid formation of dust and dust inhalation. Provide appropriate exhaust ventilation in places where dust is formed
STORAGE NEEDS	Store in original labelled container, tightly closed and in a dry, well-ventilated place.
SECTION 8: EXPOSU	URE CONTROLS / PERSONAL PROTECTION
EXPOSURE LIMITS (respirable fraction in air):	
SILICA SAND (QUARTZ)	OSHA & MSHA-PEL 10 mg/m³ (8 hour TWA) ACGIH-TLV 0.05 mg/m³ (8 hour TWA)
PORTLAND CEMENT	NIOSH 0.05 mg/m³ (10 hour TWA, 40 h work week) OSHA- PEL, ACGIH-TLV, NIOSH 5 mg/m³ (TWA)
PROTECTIVE EQUIPMENT:	
EYE / TYPE	Safety eyewear should be used when a risk assessment indicates as necessary. Avoid breathing dust. For operations where inhalation exposure can occur, a
SKIN/ BODY PROTECTION OTHER / TYPE VENTILATION REQUIREMENTS	NIOSH approved respirator may be necessary. Wear protective clothes; long sleeves and trousers to prevent dermal exposure. Eyewash fountain. Emergency shower should be in close proximity. General dilution and local exhaust as necessary to control airborne dusts below appropriate airborne concentration standards/guidelines.



	Revised October 6, 2017			
	SAFETY DATA SHEET Page 3			
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES				
PHYSICAL STATE	Powder /Granular Solid			
VAPOUR PRESSURE	Not applicable			
VISCOSITY	Not applicable			
VAPOUR DENSITY (AIR=1)	Not applicable			
SPECIFIC GRAVITY @20°C (68°F)	2.2			
BOILING POINT	Not applicable			
SOLUBILITY IN WATER	<3.0%			
APPEARANCE	Dark Grey Powder containing fine Silica Sand			
ODOUR	None			
pH LEVEL	12.5 @ 20°C (68°F) (Aqueous Solution)			
EVAPORATION RATE (N-BuAc=1)	Not applicable			
	Not applicable			
	10: STABILITY AND REACTIVITY			
CHEMICAL STABILITY	Product is stable.			
POSSIBLE HAZARDOUS REACTIONS	Hazardous polymerization will not occur under normal storage conditions.			
CONDITIONS TO AVOID	Do not allow the product to get wet as it will harden. Store in a dry place. No data available.			
INCOMPATIBLE MATERIALS HAZARDOUS DECOMPOSITION PRODUCTS:				
	Product is stable, hazardous decomposition will not occur.			
	: TOXICOLOGICAL INFORMATION			
INGREDIENTS LD50/ LC50 DATA	Refer to Page 1 Section 3.			
ROUTES OF EXPOSURE:				
EYE CONTACT	Irritating.			
SKIN CONTACT	Frequent or prolonged contact may irritate the skin, low toxicity.			
INHALATION (ACUTE)	Prolonged or repeated exposure may cause allergic reactions in certain sensitive			
CARCINOGENICITY OF MATERIAL	individuals. Respirable Silica Quartz can cause chronic silicosis. May cause cancer by inhalation. The Silica Quartz component is classified as			
CARCINOGENICIT FOR MATERIAL	carcinogenic to humans by NTP and IARC-Group 1.			
TERATOGENICITY	No data available.			
MUTAGENICITY	No data available.			
REPRODUCTIVE EFFECTS	No data available.			
OTHER	The dust product may be harmful if inhaled. Causes respiratory tract irritation.			
	Prolonged exposure can cause silicosis. May be harmful if swallowed. Causes			
	skin and eye irritation.			
SIGNS AND SYMPTOMS OF EXPOSURE	Coughing, skin rash, allergic dermatitis.			
SECTION	12: ECOLOGICAL INFORMATION			
ECOTOXICITY	No data available.			
PERSISTENCE AND DEGRADABILITY	No data available.			
BIOACCUMULATIVE POTENTIAL	No data available.			
MOBILITY IN THE SOIL	No data available.			
OTHER EFFECTS	No data available.			
SECTION	13: DISPOSAL CONSIDERATIONS			
PRODUCT DISPOSAL	Disposal of this product should comply with the requirements of environmental			
	protection and waste disposal legislation in place.			
	Do not allow product to enter sewers, streams or lakes.			
WASTE DISPOSAL	Empty containers of this product can be disposed of as normal garbage.			
SECTION 14:	TRANSPORTATION INFORMATION			
TDG CLASSIFICATION	Not regulated.			



	SAFETY DATA SHEET	Page 4				
SECTION 15: REGULATORY INFORMATION						
WHMIS CLASSIFICATION	Class E (Portland Cement)					
	Class D Division 2 Subdivision A (Silica Quartz)					
CPR (CANADA) COMPLIANCE	Meets all requirements.					
SECTION 16: OTHER INFORMATION						
ACGIH	American Confederation of Governmental Industrial Hygienists					
IARC	International Agency for Research on Cancer					
NTP	National Toxicology Program					
STEL	Short Term Exposure Limit					
PEL	Permissible Exposure Limit					
TLV-TWA	Threshold Limit Value - Time-Weighted Average					
OSHA	Occupational Safety and Health Administration					
NIOSH	National Institute for Occupational Safety and Health					
MSHA	Mine Safety and Health Administration					
CPR	Controlled Products Regulations					
CAS	Chemical Abstracts Service					
PPE	Personal Protection Equipment					
N/Av	Not available					
PREPARED BY:	Camelia Gardo					
TELEPHONE NUMBER:	(905) 669-5013					
PREPARATION DATE:	October 8th, 2017					

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.