

**SDS-403**  
**Revised October 8<sup>th</sup>, 2017**

**SAFETY DATA SHEET**

**SECTION 1: IDENTIFICATION**

**PRODUCT NAME: CIPADECK<sup>®</sup> PAVER & CONCRETE SEALER**

MANUFACTURER/SUPPLIER: ..... CPD Construction Products  
 219 Connie Crescent, Unit #13  
 Concord, Ontario Canada L4K 1L4

24 HOUR EMERGENCY NUMBER: ..... CANUTEC: (613) 996-6666

APPLICATION AND USE: ..... Paver & concrete sealing compound formulated to meet OTC – V.O.C requirements.

PRODUCT DESCRIPTION: ..... Solvent base acrylic copolymer resin sealer.

**SECTION 2: HAZARDS IDENTIFICATION**

GHS CLASSIFICATION ..... Flammable liquid- 2 ; Skin irritation- 2 ; Eye irritation -2 ; Aspiration hazard- 1 ; Specific target organ toxicity (single exposure)- 3 -central nervous system; Specific target organ toxicity (repeated exposure)- 2 - kidney, liver, spleen, blood



SIGNAL WORD ..... **DANGER**

HAZARD STATEMENTS ..... H226 Flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H320 Causes eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H373 May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS  
 PREVENTION ..... P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 P261 Avoid breathing fumes/gas/mist/vapours/spray.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/clothing/eye protection.

RESPONSE ..... P302+P362+P352 IF ON SKIN: Take off contaminated clothing. Wash with plenty of water.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P301+P310+P331 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Do NOT induce vomiting.

OTHER HAZARDS ..... Flammable vapours may spread long distances/ may ignite explosively. Use spark-proof tools and conductive shoes to avoid sparking hazards.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

Hazardous Ingredients	%	C.A.S. #	LD/50, Route, Species	LC/50, Route, Species
Acetone	30-60	67-64-1	>5,800 mg/ Kg (Oral-Rat)	
Tertiary Butyl Acetate	5-10	540-88-5	2,733 mg/ Kg (Oral-Rat) >2,000 mg/ Kg (Dermal-Rabbit)	>14,100 ppm (4hrs.) (Inhalation-Rat)
Petroleum Naphtha, Light Aromatic	10-30	64742-95-6	5,000-8,400 mg/ Kg (Oral-Rat) 14,000 mg/ Kg (Dermal-Rabbit)	3,670 ppm (4hrs.) (Inhalation-Rat)

**SAFETY DATA SHEET**

**SECTION 4 : FIRST-AID MEASURES**

**FIRST-AID MEASURES**

EYE CONTACT .....	Flush eyes with lukewarm water for at least 15 minutes. Get immediate medical attention thereafter.
SKIN CONTACT.....	Wash with soap and water and remove contaminated clothing. Wash clothing separately prior to reuse. If irritation persists, get medical attention.
INHALATION .....	Remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult give oxygen and continue to monitor. Get immediate medical attention.
INGESTION .....	If swallowed, <b>DO NOT</b> induce vomiting. Rinse mouth and call a physician or poison control centre immediately. Never give anything by mouth to an unconscious person. Stomach contents should be evacuated quickly in a manner which avoids aspiration.
<b>SYMPTOMS AND EFFECTS, ACUTE OR DELAYED</b>	
EYE CONTACT .....	Mild irritation and discomfort, may cause conjunctivitis and corneal damage when absorbed into the eye tissue.
SKIN CONTACT.....	Irritation may occur. Prolonged or repeated contact may result in skin sensitization and dermatitis due to the fatting.
INHALATION .....	Prolonged inhalation may result in respiratory irritation, dizziness, nausea and loss of consciousness. Get immediate medical attention.
INGESTION .....	Ingestion may cause severe gastrointestinal irritation, headache, nausea, vomiting
CHRONIC .....	Repeated and/or prolonged exposures may result in: adverse skin effects (de fatting, rash or allergic reaction/sensitization), adverse eye effects (conjunctivitis) and temporary liver and kidney damage.
IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED .....	Get medical attention if symptoms occur, treat symptomatically.

**SECTION 5: FIRE-FIGHTING MEASURES**

GENERAL FIRE HAZARDS .....	This product is classified as flammable category 3 (NFPA). Vapours may travel to source of ignition and flash back. Vapours may settle in low or confined spaces. May produce a floating fire hazard. Static ignition hazard can result from handling and use.
SUITABLE EXTINGUISHING MEDIA .....	Use carbon dioxide or dry chemical media for small fires. Use alcohol-type or all-purpose foam for large fires. Use water spray to cool fire exposed containers. Re-ignition is possible. Use water spray to disperse the vapours.
UNSUITABLE EXTINGUISHING MEDIA .....	No data available.
SPECIAL PROTECTION EQUIPMENT FOR FIRE FIGHTERS .....	Use self-contained breathing apparatus and protective clothing for large fires.
HAZARDOUS COMBUSTION PRODUCTS .....	Toxic gases may be formed during fire, smoke, carbon oxides, aldehydes.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES .....	Stop leak and isolate spill from all ignition sources. Avoid all contact with eyes, skin or clothing. Do not breath in vapours or fumes. Use appropriate personal protection equipment (PPE).
ENVIRONMENTAL PRECAUTIONS .....	Prevent entry to drains, sewers and public waters.
CONTAINMENT AND CLEAN UP .....	Contain/absorb spilled product with dry sand or earth. Do not use combustible materials such as sawdust. Dispose of clean up materials as hazardous waste in accordance with all provincial, state and federal laws.

**SECTION 7: HANDLING AND STORAGE**

PRECAUTIONS FOR SAFE HANDLING .....	Ground containers when transferring to sprayers. Keep containers closed when not in use. Keep containers out of direct sunlight. Once product is used, leave container lids off to allow all solvent to evaporate.
-------------------------------------	--

**SAFETY DATA SHEET**

CONDITIONS FOR SAFE STORAGE ..... Store in a cool dry area out of direct sunlight and away from all sources of ignition. Open pails containing product must be sealed prior to storing. **DO NOT** store full or part pails in direct sunlight.

**SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**

OCCUPATIONAL EXPOSURE LIMITS:

ACETONE .....	<u>ACGIH TLV</u> TWA-250 ppm STEL-500 ppm	<u>OSHA PEL</u> TWA-1800 mg/m <sup>3</sup> STEL-2400 mg/m <sup>3</sup>	<u>NIOSH IDLH</u> IDLH-2500 ppm TWA-250 ppm TWA-590 mg/m <sup>3</sup>
---------------	---	--	--

TERTIARY BUTYL ACETATE .....	<u>ACGIH TLV</u> TWA-200 ppm	<u>OSHA PEL</u> TWA-200 ppm TWA-950 mg/m <sup>3</sup>	<u>NIOSH</u> TWA-200 ppm TWA-950 mg/m <sup>3</sup>
------------------------------	---------------------------------	---	--

APPROPRIATE ENGINEERING CONTROL ..... Good ventilation should be assured to maintain vapours concentration below exposure limits. A portable eye wash station is recommended at the job site.

PERSONAL PROTECTIVE EQUIPMENT:

EYE / TYPE ..... Splash proof chemical goggles are recommended.

RESPIRATORY PROTECTION ..... Concentrations in air determine the level of respirator protection needed. Use only NIOSH certified equipment. A half mask air purifying respirator with organic vapour cartridge is recommended.

GLOVES/TYPE ..... Neoprene or natural rubber gloves are required for protection of hands.

CLOTHING/TYPE ..... Standard coveralls. Always remove any contaminated clothing and wash before reuse.

FOOTWEAR/TYPE ..... Solvent resistant safety shoes/boots.

OTHER INFORMATION ..... Do not eat, drink or smoke when handling this material.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE .....	Liquid
APPEARANCE .....	Clear or slight yellow
ODOUR .....	Camphor like odour
ODOUR THRESHOLD .....	71 ppb
pH LEVEL .....	Not applicable
EVAPORATION RATE .....	6.3 (Butyl Acetate =1)
BOILING POINT .....	56°C (133°F) Acetone
FREEZING/MELTING POINT .....	Not Available
FLASH POINT (deg C), METHOD.....	-20°C (-4°F) Tag Closed Cup (TCC)
FLAMMABLE LIMITS IN AIR .....	2.15 - 13.0% (by volume)
AUTO IGNITION TEMPERATURE (deg C) ....	465°C (869°F)
VAPOUR PRESSURE (mmHg).....	180 @ 20°C (68°F)
VAPOUR DENSITY .....	2.0 (air=1.0)
SOLUBILITY IN WATER .....	Insoluble
SPECIFIC GRAVITY @20°C (68°F).....	0.870
V.O.C. Content .....	< 350 grams/L
PERCENT SOLIDS .....	25 -28%

**SECTION 10: STABILITY AND REACTIVITY**

REACTIVITY ..... Stable under normal use conditions.

CHEMICAL STABILITY ..... Material is stable under normal use conditions.

POSSIBILITY OF HAZARDOUS REACTIONS: ..... Hazardous polymerization will not occur under normal conditions.

CONDITIONS TO AVOID ..... Avoid direct sunlight, heat, sparks, open flame or other ignition sources.

INCOMPATIBLE MATERIALS ..... Avoid contact with strong acids and strong oxidizing compounds.

HAZARDOUS DECOMPOSITION PRODUCTS: ..... Carbon oxides (CO, CO<sub>2</sub>), smoke, aldehydes.

**SAFETY DATA SHEET**

**SECTION 11: TOXICOLOGICAL INFORMATION**

**EXPOSURE ROUTES/ SYMPTOMS AND EFFECTS**

INGESTION .....	Product may be harmful or fatal if swallowed. Ingestion may cause central nervous system effects including dizziness, unconsciousness, coma or death.
INHALLATION .....	High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness and even death). High vapour concentrations are irritating for eyes, nose, throat, lungs.
EYE CONTACT .....	Contact with the eye may cause moderate to severe irritation.
SKIN CONTACT .....	Moderately irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis.
PRE-EXISTING CONDITIONS .....	The following diseases or disorders may be aggravated by exposure to this product: skin, eye, lung (asthma-like conditions).
CARCINOGENICITY OF MATERIAL .....	Not applicable.
REPRODUCTIVE EFFECTS .....	No data available.

**SECTION 12: ECOLOGICAL INFORMATION**

ECOTOXICITY .....	No data available.
PERSISTENCE AND DEGRADABILITY .....	This product is not expected to persist in the environment.
BIOACCUMULATIVE POTENTIAL .....	No data available.
MOBILITY IN THE SOIL .....	No data available.

**SECTION 13: DISPOSAL CONSIDERATIONS**

PRODUCT DISPOSAL .....	Recover and recycle if possible. Otherwise: incineration in a permitted facility. Product in the liquid state is hazardous material and must be disposed of in accordance with all Provincial, State and Federal laws. Do not allow product to enter sewers, streams or lakes.
WASTE DISPOSAL .....	Empty containers of this product that are dry (no solvent) can be disposed of as normal garbage.

**SECTION 14: TRANSPORTATION INFORMATION**

TDG CLASSIFICATION .....	<b>Paint Related Material, UN1263, Class 3, PG II</b>
--------------------------	---

**SECTION 15: REGULATORY INFORMATION**

WHMIS CLASSIFICATION .....	B2, D2A, D2B
CPR (CANADA) COMPLIANCE .....	Meets all requirements.

**SECTION 16: OTHER INFORMATION**

ACGIH .....	American Confederation of Governmental Industrial Hygienists
IARC.....	International Agency for Research on Cancer
NTP.....	National Toxicology Program
STEL .....	Short Term Exposure Limit
PEL .....	Permissible Exposure Limit
TLV-TWA .....	Threshold Limit Value - Time-Weighted Average
OSHA .....	Occupational Safety and Health Administration
NIOSH .....	National Institute for Occupational Safety and Health
MSHA .....	Mine Safety and Health Administration
CPR .....	Controlled Products Regulations
CAS .....	Chemical Abstracts Service
PREPARED BY: .....	Camelia Gardo
TELEPHONE NUMBER: .....	(905) 669-5013
PREPARATION DATE: .....	October 8 <sup>th</sup> , 2017

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.