MasterFormat® 03 15 10



CPD® WATERSTOP

RIBBED CENTER BULB	HEAD OF WATER-FT.	WT. LBS. 100 LIN. FT.	TYPE OF APPLICATION
CATALOG NUMBER, SHAPE AND DIMENSIONS			
RCB-4316CA (Type 3) 4" 7/16" I.D. 5/16" O.D. 3/4"	100	68	This model is used in construction for higher heads of water than Type 3A handles.
RCB-4316 (Type 3A) 4" 7/16" 1.D. 5/16" 3/16"	65	48	This model is used in construction joints for building sub-structures, swimming pools, water tanks, etc.
RCB-6316NT (Type 4) 6 "	125	90	Used in filtration plants and heavily used water treatment plants.
RCB-6316 (Type 4B) 6 " 7/16" I.D. 5/16" O.D. 9/16" 3/16"	100	74	This model is used in construction for higher heads of water than Type 3A handles.
RCB-638 (Type 5) 6 " 7/16" 1.D. 5/16" 3/8"	125	115	This model can be used above grade or below grade. This is one of our most ordered bulb shapes.
RCB-938 (Type 7) 9 " 3/8"¬ 3/16"¬ I.D. 3/8"	150	168	For use in large, primary structures that must handle exceptionally high heads of watersewage plants, dams, large reservoirs, locks, etc.
RCB-938LB (Type 7C) 9 " I.D. 3/4" O.D. 1 1/4" 1/2"	150	225	Use this model on jobs where extra movement is expected in above grade expansion joints.

Rev. 12.18