

SDS-78
Revised July 8th, 2026

SAFETY DATA SHEET

Page 1

SECTION 1: IDENTIFICATION

PRODUCT NAME: # 906 GEL EPOXY (GREY) PART "B"

MANUFACTURER/SUPPLIER: CPD Construction Products
219 Connie Crescent, Unit #13
Concord, Ontario Canada L4K 1L4

24 HOUR EMERGENCY NUMBER: CANUTEC: (613) 996-6666

APPLICATION AND USE: Epoxy adhesive gel and mortar binder.

PRODUCT DESCRIPTION: Two components 100 % solids low temperature cure epoxy adhesive gel.

SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION: Skin corrosion/ irritation- Category 1B; Serious eye damage/ eye irritation- Category 1; Skin sensitization- Category 1A; Reproductive Toxicity- Category 2; Specific target organ toxicity, single exposure- Category 3 (Respiratory irritation) Specific target organ toxicity- repeated exposure- Category 2



SIGNAL WORD: **DANGER**

HAZARD STATEMENTS: H314 Causes severe skin burns and eye damage.
H317 May cause allergic skin reaction.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H360 May damage fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:
PREVENTION P201 Obtain special instruction before use.
P202 Do not handle until all safety precautions have been read and understood.
P271 Use only outdoors or in a well-ventilated area.
P260 Do not breathe dust or mist.
P272 Contaminated work clothing should not be allowed out of the workplace.
P264 Wash thoroughly after handling.
P280 Wear protective gloves/ clothing and eye/face protection.

RESPONSE P308+P313+P311 If exposed or concerned: Get medical attention/ advice. Call a POISON CENTER or doctor/ physician.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P301+ P330+P331+315 IF SWALLOWED: Rinse mouth. Do not induce vomiting. Get immediate medical advice/ attention.

STORAGE P405 Store locked up.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

OTHER HAZARDS: Ingestion can cause gastrointestinal irritation, nausea and diarrhea. Prolonged inhalation may cause adverse lung effects with symptoms including coughing, mucous production and difficulty breathing.
Burning produces obnoxious and toxic fumes.

SDS-78
Revised July 8th, 2026

SAFETY DATA SHEET				Page 2
SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS				
Hazardous Ingredients	%	C.AS. #	LD/50, Route, Species	LC/50, Route, Species
Phenalkamine Curing Agent	20-30	Mixture	Not available	Not Available
Polymer of C-18 Unsaturated Fatty Acid	15-25	68082-29-1	2001 mg/Kg (Oral-Rat)	Not Available
N-Aminoethyl Piperazine	5-10	140-31-8	2150 mg/ Kg (Oral-Rat) 880 mg/ Kg (Dermal-Rabbit)	Not Available
Bisphenol A	3-7	80-05-7	3300 mg/ Kg (Oral-Rat) 3600 mg/ Kg (Dermal-Rabbit)	Not Available
Nonyl Phenol	1-5	25154-52-3	1540 mg/ Kg (Oral-Rat) 2000 mg/ Kg (Dermal-Rabbit)	Not Available
Tris, 2,4,6-Dimethyl Aminomethyl Phenol	1-5	90-72-2	1200 mg/ Kg (Oral-Rat)	Not Available
Triethylene Tetramine	1-5	112-24-3	4340 mg/ Kg (Oral-Rat) 805 mg/ Kg (Dermal-Rabbit)	Not Available
Benzyl Alcohol	1-5	100-51-6	1230mg/Kg. (Oral-Rat)	Not Available
SECTION 4: FIRST-AID MEASURES				
FIRST-AID MEASURES				
EYE CONTACT	Immediately call a POISON CENTRE or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.			
SKIN CONTACT.....	Immediately call a POISON CENTRE or doctor/physician. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.			
INHALATION	Immediately call a POISON CENTRE or doctor/ physician. IF INHALED: remove person to fresh air and keep comfortable for breathing. If breathing has stopped give artificial respiration. If breathing is difficult give oxygen by qualified medical personnel only.			
INGESTION	Immediately call a POISON CENTRE or doctor/ physician. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Never give anything by mouth to an unconscious person.			
SYMPTOMS AND EFFECTS, ACUTE OR DELAYED				
EYE CONTACT	Causes severe eye damage.			
SKIN CONTACT	Harmful in contact with skin. May be absorbed through the skin. Corrosive to all tissues. Causes severe skin burns. Direct skin contact may cause corrosive skin burns, deep ulcerations and possibly permanent scarring. May cause an allergic skin reaction (e.g. swelling, rash and eczema) Allergic symptoms may develop within 12 hours after exposure.			
INHALATION	Harmful if inhaled. May cause respiratory irritation. If mists are formed, may cause severe irritation to the nose, throat and respiratory tract. Symptoms may include coughing, chest pain and shortness of breath.			
INGESTION	Ingestion can cause irritation and corrosive action in the mouth, stomach and digestive tract. Symptoms include: Gastrointestinal discomfort, nausea, vomiting, cramping and diarrhea. Suspected of damaging fertility or the unborn child.			
IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	Treat symptomatically.			

SDS-78
Revised July 8th, 2026

SAFETY DATA SHEET

Page 3

SECTION 5: FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA	Carbon dioxide (CO ₂), dry chemical or alcohol foam.
UNSUITABLE EXTINGUISHING MEDIA	Do not use a solid water stream as it may scatter and spread fire.
SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE	Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.
FLAMMABILITY CLASSIFICATION	Not flammable, according to OSHA 29 CFR 1910.106.
HAZARDOUS COMBUSTION PRODUCTS	Carbon oxides. Nitrogen oxides, Hydrogen cyanide, Ammonia, Amines, Aldehydes, Ketones and other irritating fumes and smoke.
FIRE-FIGHTERS PROTECTIVE EQUIPMENT ...	Fire-fighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots and in enclosed spaces, fire-fighters should wear an approved full face, self-contained breathing apparatus (SCBA) and impervious clothing.
SPECIAL FIRE FIGHTING PROCEDURES.....	Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Do not allow run-off from the firefighting to enter drains or water courses. Dike for water control.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES	Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Refer to Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.
ENVIRONMENTAL PRECAUTIONS	Ensure spilled product does not enter drains, sewers, waterways or confined spaces. For large spills, dike the area to prevent spreading.
METHODS AND MATERIAL FOR CONTAINMENT AND CLEAN-UP	Ventilate the area. Remove all sources of ignition. Stop the spill at source if it is safe to do so. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand). Pick up and transfer to properly labelled containers. Refer to Section 13 for disposal of contaminated material. Contact the proper local authorities.
SPECIAL SPILL RESPONSE PROCEDURES ...	If a spill/ release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response centre or the appropriate local authorities.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	Obtain special instruction before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Persons with recurring skin eczema or sensitization problems should be excluded from working with this product. Once a person is sensitized, no further exposure to the material that caused the sensitization should be permitted. Wear protective gloves/ clothing and eye/ face protection. Contaminated work clothing must not be allowed out of the workplace. Do not breath dust or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Wash thoroughly after handling. Keep containers tightly closed when not in use. Keep away from extreme heat and flame. Take precautions to prevent premature mixing of components and subsequent premature curing.
CONDITIONS FOR SAFE STORAGE	Store locked up. Keep containers tightly closed. Store in a well-ventilated place. Store away from incompatible materials. Inspect periodically for damage or leaks. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. No smoking in the area.

SDS-78
Revised July 8th, 2026

SAFETY DATA SHEET

Page 4

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS:	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
TRIETHYLENETETRAMINE	1 ppm (skin) (AIHA WEEL)	N/Av	N/Av	N/Av
BENZYL ALCOHOL	10 ppm (AIHA WEEL)	N/Av	N/Av	N/Av
EXPOSURE CONTROLS:	Use only in well ventilated areas. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If airborne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29CFR 1910.134) or CSA Z94.4-02. NIOSH approved organic vapour cartridge respirators are recommended. Advice should be sought from respiratory protection specialists. Wear protective gloves/ clothing. Gloves impervious to the material are recommended. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Wear eye/ face protection. Chemical splash goggles are recommended. A full face shield may also be necessary. An eyewash station and safety shower should be made available in the immediate working area. Other equipment may be required depending on workplace standards. Do not eat, drink, smoke or use cosmetics while working with this product. Do not breath dust or mist. Avoid contact with eyes, skin and clothing. Barrier creams may help to protect the exposed areas of skin; they should however not be applied once exposure has occurred. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Contaminated clothing must not be allowed out of the workplace.			
VENTILATION/ ENGINEERING MEASURES:				
RESPIRATORY PROTECTION				
SKIN PROTECTION				
EYE/ FACE PROTECTION				
OTHER PROTECTIVE EQUIPMENT				
GENERAL HYGIENE CONSIDERATIONS				

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE	Semi-solid gel
COLOUR	Black
ODOUR	Characteristic Amine
pH LEVEL	Not available
MELTING/ FREEZING POINT	Not available
BOILING POINT	Not available
FLASH POINT	Not available
EVAPORATION RATE	Not available
FLAMMABILITY	Not applicable
VAPOUR PRESSURE	Not available
RELATIVE VAPOUR DENSITY (Air=1) (mg/m3)	Not available
SPECIFIC GRAVITY @ 20°C (68°F)	1.02
VISCOSITY	Not available
VOLATILES (% by WEIGHT)	Not available
VOC's (Volatile Organic Compounds)	0 grams/ L
SOLUBILITY IN WATER (%W/W)	Insoluble
PARTICLE CHARACTERISTICS	Not available

SDS-78
Revised July 8th, 2026

SAFETY DATA SHEET

Page 5

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY	Not normally reactive.
CHEMICAL STABILITY	Stable under the recommended storage and handling conditions prescribed.
HAZARDOUS REACTIONS	Hazardous polymerization does not occur.
CONDITIONS TO AVOID	Avoid heat and open flame. Avoid contact with incompatible materials. Ensure adequate ventilation, especially in confined areas.
INCOMPATIBLE MATERIALS	Acids. Oxidizing agents. Acid chlorides. Acid anhydrides. Aldehydes. Ketones. Acrylates.
HAZARDOUS DECOMPOSITION PRODUCTS	Refer to hazardous combustion products, Section 5.

SECTION 11: TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF EXPOSURE	Skin and eye contact, inhalation, ingestion.
SIGNS AND SYMPTOMS OF EXPOSURE	
SKIN CONTACT	Harmful in contact with skin. May be absorbed through the skin. Corrosive to all tissues. Causes severe skin burns. Direct skin contact may cause corrosive skin burns, deep ulcerations and possibly permanent scarring.
EYE CONTACT	Corrosive to eyes. Causes serious eye damage. Direct eye contact may produce severe irritation with possible eye damage.
INHALATION	May cause respiratory irritation. If mists are formed, may cause severe irritation to the nose, throat and respiratory tract. Symptoms may include coughing, chest pain and shortness of breath.
INGESTION	Ingestion can cause irritation and corrosive action in the mouth, stomach and digestive tract. Symptoms include: Gastrointestinal discomfort, nausea, vomiting, cramping and diarrhea.
CHRONIC HEALTH EFFECTS	Prolonged inhalation may cause adverse lung effects with symptoms including coughing, mucous production and difficulty breathing. Prolonged or repeated overexposure may cause kidney effects.
MUTAGENICITY	Not expected to be mutagenic in humans.
CARCINOGENICITY	No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP
REPRODUCTIVE EFFECTS	This material is classified as hazardous under U.S. OSHA regulations (29 CFR1910.1200) (Hazcom2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015) Classification: Reproductive Toxicity- Category 1 May damage fertility or the unborn child.
SENSITIZATION TO MATERIAL	This material is classified as hazardous under U.S. OSHA regulations (29 CFR1910.1200) (Hazcom2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015) Classification: Skin sensitization- Category 1A- May cause allergic skin reaction. Respiratory sensitization- Category 1- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
SPECIFIC TARGET ORGAN EFFECTS	This material is classified as hazardous under U.S. OSHA regulations (29 CFR 1910.1200) (Hazcom2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015) Classification: Specific target organ toxicity, single exposure-Category 3 respiratory irritation. Specific target organ toxicity, repeated exposure- Category 2 damage to organs (kidneys)
MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE	Pre-existing skin, eye, and respiratory disorders.
TOXICOLOGICAL DATA	There is no data available for this product.
INGREDIENTS LD50/ LC50 DATA	Refer to Section 3.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY	Toxic to aquatic life with long lasting effects. Do NOT allow product to come in contact with surface waters. Avoid release into environment.
PERSISTANCE AND DEGRADABILITY	No data is available on the product itself.
BIOACCUMULATION POTENTIAL	No data is available on the product itself.
MOBILITY IN SOIL	No data is available on the product itself.

SDS-78
Revised July 8th, 2026

SAFETY DATA SHEET		Page 6
SECTION 13: DISPOSAL CONSIDERATIONS		
HANDLING FOR DISPOSAL	Handle in accordance with good industrial hygiene and safety practice. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Refer to protective measures listed in Sections 7 and 8.	
METHODS OF DISPOSAL	Dispose in accordance with all applicable federal, state, provincial and local regulations.	
SECTION 14: TRANSPORTATION INFORMATION		
TDG CLASSIFICATION	Polyamines, Liquid, Corrosive, N.O.S. UN 2735, Class 8, PG III	
SECTION 15: REGULATORY INFORMATION		
WHMIS CLASSIFICATION	Class D, Division 2, Subdivision B Class E, Corrosive	
CPR (CANADA) COMPLIANCE	Meets all requirements.	
SECTION 16: OTHER INFORMATION		
ACGIH	American Confederation of Governmental Industrial Hygienists	
IARC.....	International Agency for Research on Cancer	
NTP.....	National Toxicology Program	
STEL	Short Term Exposure Limit	
PEL	Permissible Exposure Limit	
TLV-TWA	Threshold Limit Value - Time-Weighted Average	
OSHA	Occupational Safety and Health Administration	
NIOSH	National Institute for Occupational Safety and Health	
MSHA	Mine Safety and Health Administration	
RCRA	Resource Conservation and Recovery Act	
CPR	Controlled Products Regulations	
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act	
CAS	Chemical Abstracts Service	
PPE	Personal Protection Equipment	
PREPARED BY:	Camelia Gardo	
TELEPHONE NUMBER:	(905) 669-5013	
PREPARATION DATE:	July 8 th , 2026	
The above information pertains to this product as currently formulated and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.		