

SDS-264
Revised July 8th, 2026

SAFETY DATA SHEET

Page 1

SECTION 1: IDENTIFICATION

PRODUCT NAME: CIPADAM® S-40

MANUFACTURER/SUPPLIER: CPD Construction Products
219 Connie Crescent, Unit #13
Concord, Ontario Canada L4K 1L4

24 HOUR EMERGENCY NUMBER: CANUTEC: (613) 996-6666

APPLICATION AND USE: Protects concrete and masonry surfaces from moisture intrusion. Spray, brush or broom applied.

PRODUCT DESCRIPTION: Water repellent silane based sealer.

SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION Flammable Liquid, (Category 2), Serious eye damage/ irritation (Category 2B)



SIGNAL WORD **DANGER**

HAZARD STATEMENTS H225 Highly flammable liquid and vapour.

PRECAUTIONARY STATEMENTS

PREVENTION P202 Do not handle until all safety precautions have been read and understood
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breath mist/ vapours/ spray.
P262 Do not get in eyes, on skin or on clothing.
P264 Wash thoroughly after handling.

RESPONSE P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303+P361+ P353 If ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P331 Do NOT induce vomiting.

OTHER HAZARDS Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	%	C.A.S. #	LD/50, Route, Species	LC/50, Route, Species
N-Octyltriethoxy Silane	15-40	2943-75-1	>5110 mg/ Kg (Oral-Rat)	Not Available
Tertiary Butyl Acetate	60-100	540-88-5	2733 mg/ Kg (Oral-Rat) >2000 mg/ Kg (Dermal-Rabbit)	>14,100ppm (4hrs.) (Inhalation-Rat)
Ethyl Alcohol	3 – 7	64-17-5	7060 mg/ Kg (Oral-Rat) 20,000 mg/ Kg (Dermal-Rabbit)	31,624ppm (4hrs.) (Inhalation-Rat)
2-Methylpropan-2-ol	0.1-1.0	75-65-0	3500 mg/ Kg (Oral-Rat)	Not available

SDS-264
Revised July 8th, 2026

SAFETY DATA SHEET

Page 2

SECTION 4 : FIRST-AID MEASURES

FIRST-AID MEASURES

EYE CONTACT	Immediately flush eyes with large quantities of water lifting upper and lower eyelids occasionally. Get immediate medical attention.
SKIN CONTACT.....	Wash with soap and water. Remove contaminated clothing and do not reuse until laundered. If persistent irritation occurs, get medical attention.
INHALATION	Remove victim to fresh air. Give artificial respiration if not breathing. Keep person warm, quiet and get immediate medical attention if unconscious.
INGESTION	Drink 1 to 2 glasses of water to dilute. Do not induce vomiting even though vomiting may occur. If vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs which can cause chemical pneumonitis, which is fatal. Get immediate medical attention.
ADDITIONAL INFORMATION	In all cases, if irritation persists seek medical attention. The following diseases or disorders may be aggravated by exposure to this product: skin, eye, lung (asthma-like conditions).
MOST IMPORTANT SYMPTOMS/ EFFECTS, ACUTE OR DELAYED	Effects of over exposure: overexposure can lead to central nervous system depression producing such effects as headaches, dizziness, nausea and loss of consciousness and even asphyxiation.
IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	Get medical attention if symptoms occur.

SECTION 5: FIRE-FIGHTING MEASURES

GENERAL FIRE HAZARDS.....	Vapours may form an explosive mixture with air. Closed containers may rupture when exposed to extreme heat.
SUITABLE EXTINGUISHING MEDIA	Use carbon dioxide or dry chemical media for small fires. Use alcohol-type or all-purpose foam for large fires.
UNSUITABLE EXTINGUISHING MEDIA	Do not use solid water stream as this may spread fire.
SPECIAL PROTECTION EQUIPMENT FOR FIRE FIGHTERS	Exposure to vapours or products of combustion should be avoided. Fire-fighters should use a self-contained breathing apparatus and full protective clothing in case of fire.
HAZARDOUS COMBUSTION PRODUCTS	Smoke, fumes, aldehydes and oxides of carbon.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, EMERGENCY PROCEDURES ...	Eliminate source of ignition. Keep public away. Dike area to prevent spreading. Wear appropriate respirator and other protective clothing. Shut off source of leak only if safe to do so. Dike and contain. Remove with explosion proof equipment.
ENVIRONMENTAL PRECAUTIONS	Prevent runoff material into drains, sewers and other waterways. Collect flush solution in drums. Dispose of as hazardous waste.
CONTAINMENT AND CLEAN UP	Cover spill with inert material. Soak up residue with non-combustible absorbent such as clay or vermiculite; place in drums for proper disposal. Flush area with water to remove trace residue. Collect for proper disposal. Wash area with soapy water and rinse thoroughly. Dispose of in a facility approved under government regulations for hazardous waste. Containers must be leak-proof and properly labelled.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	Keep containers tightly closed when not in use. Ground all equipment and use only spark proof tools and conductive shoes. Wash thoroughly before eating, drinking, smoking or using toilet facilities. Launder contaminated clothing before reuse. Containers, even those that have been emptied, retain product residue (vapours and/or liquid). Always obey hazard warning and handle empty containers as if they were full. Do not smoke when using this product.
-------------------------------------	--

SDS-264
Revised July 8th, 2026

SAFETY DATA SHEET

Page 3

CONDITIONS FOR SAFE STORAGE	Store in original labelled container, away from oxidizing materials in a cool dry place with adequate ventilation. Protect from heat and open flames.
-----------------------------------	---

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMIT:	<u>ACGIH</u>	<u>OSHA</u>	<u>NIOSH</u>
N-OCTYLTRIETHOXY SILANE	1000 ppm TWA 1000 ppm STEL	Not Available	Not Available
TERTIARY BUTYL ACETATE	200 ppm TWA	Not Available	1500 ppm IDLH
ETHYL ALCOHOL	1000 ppm TWA 1000 ppm STEL	Not Available	Not Available
2-METHYLPROPAN-2-OL	100 ppm TWA-TLV	100 ppm PEL	Not Available
APPROPRIATE ENGINEERING CONTROL	General (dilution) ventilation is required during normal use. Local exhaust ventilation may be required during certain operations to keep exposure level below the limit listed above.		
PERSONAL PROTECTIVE EQUIPMENT:			
EYE / TYPE	Splash proof chemical goggles are recommended.		
RESPIRATORY PROTECTION	Concentrations in air determine the level of respirator protection needed. Use only NIOSH certified equipment. A half mask air purifying respirator with organic vapour cartridge is recommended.		
GLOVES/TYPE	Neoprene or natural rubber gloves are required for protection of hands.		
CLOTHING/TYPE	Standard coveralls. Always remove contaminated clothing and wash before reuse		
FOOTWEAR/TYPE	Solvent resistant safety shoes/boots.		
OTHER	A portable eye wash station is recommended where this product is being applied.		

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE	Liquid
ODOUR	Camphor like odour
ODOUR TRESHOLD	71 ppb (TBAC)
COLOUR	Clear
pH LEVEL	Not applicable
FREEZING/ MELTING POINT	Not available
BOILING POINT	98°C (208°F) TBAC
FLASH POINT	4.4°C (39.92°F) Tag Closed Cup (TCC)
AUTO IGNITION TEMPERATURE (deg C)	Not available.
UPPER FLAMMABLE LIMIT (% VOL)	Not available.
LOWER FLAMMABLE LIMIT (% VOL)	Not available.
VAPOUR PRESSURE	31 @ 20°C (68°F)
VAPOUR DENSITY (AIR=1)	0.862
RELATIVE DENSITY @ 20°C (68°F)	0.86 (approx.)
EVAPORATION RATE	2.8 (ButylAcetate =1)
SOLUBILITY IN WATER	Not available
VISCOSITY	10 cps @ 20°C (68°F) (Approx.)
KINEMATIC VISCOSITY	No data available
V.O.C.	350 gm/L
PARTICLE CHARACTERISTICS	No data available

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY	No data available.
CHEMICAL STABILITY	Stable under normal temperatures and pressures. Hazardous polymerization has not been reported.
POSSIBILITY OF HAZARDOUS REACTIONS:	Material will react with water liberating ethanol.
CONDITIONS TO AVOID	Avoid heat, sparks and open flame. Avoid moist air and water contact.
INCOMPATIBLE MATERIALS	Strong oxidizing compounds.
HAZARDOUS DECOMPOSITION PRODUCTS:	Ethanol in case of hydrolysis.

SDS-264
Revised July 8th, 2026

SAFETY DATA SHEET		Page 4
SECTION 11: TOXICOLOGICAL INFORMATION		
EXPOSURE ROUTES/ SYMPTOMS AND EFFECTS		
EYE CONTACT	Short-term liquid or vapour contact may result in eye irritation. Prolonged and repeated contact will be more irritating.	
SKIN CONTACT	Prolonged and repeated liquid contact can cause defatting and drying of the skin which may result in skin irritation and dermatitis.	
INHALATION (ACUTE)	High concentrations or prolonged exposure to lower concentrations may be irritating to mucous membrane.	
INGESTION	Liquid ingestion may result in vomiting. Aspiration of liquid into the lungs must be avoided as liquid contact with the lungs can result in chemical pneumonitis and pulmonary edema/haemorrhage.	
EFFECTS OF CHRONIC EXPOSURE:	Effects of over exposure: overexposure can lead to central nervous system depression producing such effects as headaches, dizziness, nausea and loss of consciousness and even asphyxiation.	
CARCINOGENICITY OF MATERIAL	This product is not listed by NTP, IARC or regulated as a carcinogen by OSHA.	
TERATOGENICITY	No data available.	
MUTAGENICITY	No data available.	
REPRODUCTIVE EFFECTS	No data available.	
SECTION 12: ECOLOGICAL INFORMATION		
ECOTOXICITY	No data available.	
PERSISTANCE AND DEGRADABILITY	This product is not expected to persist in the environment.	
BIOACCUMULATIVE POTENTIAL	No data available.	
MOBILITY IN THE SOIL	No data available.	
SECTION 13: DISPOSAL CONSIDERATIONS		
WASTE DISPOSAL	Product in the liquid state is hazardous material and must be disposed of as in accordance with all Provincial, State and Federal laws.	
CONTAMINATED PACKAGING	Empty containers of the product that are dry (no solvent) can be disposed of as normal garbage.	
SECTION 14: TRANSPORTATION INFORMATION		
TDG CLASSIFICATION	Paint Related Material, UN1263, Class 3, PG II	
SECTION 15: REGULATORY INFORMATION		
WHMIS CLASSIFICATION	B2, D-2B	
SECTION 16: OTHER INFORMATION		
ACGIH	American Confederation of Governmental Industrial Hygienists	
IARC.....	International Agency for Research on Cancer	
NTP.....	National Toxicology Program	
STEL	Short Term Exposure Limit	
PEL	Permissible Exposure Limit	
TLV-TWA	Threshold Limit Value - Time-Weighted Average	
OSHA	Occupational Safety and Health Administration	
NIOSH	National Institute for Occupational Safety and Health	
CPR	Controlled Products Regulations	
CAS	Chemical Abstracts Service	
PREPARED BY:	Camelia Gardo	
TELEPHONE NUMBER:	(905) 669-5013	
PREPARATION DATE:	July 8 th , 2026	
The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.		