

SDS-27
Revised July 9th, 2026

SAFETY DATA SHEET

Page 1

SECTION 1: IDENTIFICATION

PRODUCT NAME: CIPADITE® E-500 GROUT AGGREGATE

MANUFACTURER/SUPPLIER: CPD Construction Products
219 Connie Crescent, Unit #13
Concord, Ontario Canada L4K 1L4

24 HOUR EMERGENCY NUMBER: CANUTEC: (613) 996-6666

PRODUCT IDENTIFIER: CIPADITE® E-500 Grout Aggregate (Special Note): CIPADITE® E-500 Grout is a three-component product. This SDS is only for the aggregate component. See separate SDS's for the resin component and hardener component. This product has 3 Safety Data Sheets.

APPLICATION AND USE: High strength grout for base plates, anchor bolts, columns etc., where either very high strengths and/or chemical resistance are required.

PRODUCT DESCRIPTION: Silica filled thermosetting Epoxy Compound. This component is the Silica Aggregate Component only.

SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION: Carcinogenicity 1A (Inhalation); Specific target organ toxicity- Repeated exposure 1, Lungs



SIGNAL WORD: **DANGER**

HAZARD STATEMENTS: H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
H350 May cause cancer by inhalation
H372 Causes damage to organs (Lung) through prolonged or repeated exposure

PRECAUTIONARY STATEMENTS:
PREVENTION P260 Do not breathe dust
P264 Wash hands thoroughly after handling
P270 Do not eat, drink or smoke when using this product
P281 Use personal protective equipment as required
P284 In case of inadequate ventilation, wear respiratory protection

RESPONSE P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P308+P313 If exposed or concerned: Get medical advice/ attention

OTHER HAZARDS: Not available.

UNKNOWN ACUTE TOXICITY: Not available.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	%	C.A.S. #	LD/50, Route, Species	LC/50, Route, Species
Silica Sand ** Quartz	60-100	14808-60-7	Not Available	Not Available

** The sand used in this product contains Quartz. The Quartz that exists as particles with Aerodynamic Diameter less than 5 microns is hazardous. An approved dust mask (for Crystalline Silica) should be worn by workers when handling this product in the dry state.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SDS-27
Revised July 9th, 2026

SAFETY DATA SHEET

Page 2

SECTION 4 : FIRST-AID MEASURES

FIRST-AID MEASURES

EYE CONTACT	Remove contact lenses if present and easy to do so. Rinse with plenty of water, keeping the eyelids wide open.
SKIN CONTACT	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.
INHALATION	Move to fresh air. Consult a physician after significant exposure.
INGESTION	Immediately clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Do not give milk or other alcoholic beverages. Never give anything by mouth to an unconscious person.
SYMPTOMS AND EFFECTS, ACUTE OR DELAYED	Carcinogenic effects. May cause cancer by inhalation. Causes damage to organs (Lung) through prolonged or repeated exposure.
NOTE TO THE PHYSICIAN	Present this material safety data sheet to the doctor in attendance. Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA	This product will not burn. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
UNSUITABLE EXTINGUISHING MEDIA	No available information.
SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE	Not applicable
FLAMMABILITY CLASSIFICATION	Not flammable.
HAZARDOUS COMBUSTION PRODUCTS	None.
FIRE-FIGHTERS PROTECTIVE EQUIPMENT ...	In the event of fire, wear self-contained breathing apparatus.
SPECIAL FIRE FIGHTING PROCEDURE	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES	Use personal protective equipment. Avoid breathing dust. Deny access to unprotected persons.
ENVIRONMENTAL PRECAUTIONS	Do not flush into surface water or sanitary sewer system. For significant spillages advise local authorities.
METHODS AND MATERIAL FOR CONTAINMENT AND CLEAN-UP	Pick-up and arrange disposal without creating dust. Keep in suitable, closed containers for proper disposal.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	Avoid formation of respirable particles. Avoid exceeding the given occupational exposure limits as listed in Section 8. Do not get in eyes, on skin or on clothing. For personal protection refer to Section 8. Smoking, eating and drinking should be prohibited in the application area.
CONDITIONS FOR SAFE STORAGE	Product should be stored off the ground. May be stored outside or inside under tarp. Do not allow bags of aggregate to get wet. Aggregate cannot be used if wet.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS (respirable fraction in air):	
SILICA SAND (QUARTZ)	OSHA & MSHA-PEL 10 mg/m ³ (8-hour TWA) ACGIH-TLV 0.05 mg/m ³ (8-hour TWA) NIOSH 0.05 mg/m ³ (10-hour TWA, 40 h work week)

SDS-27
Revised July 9th, 2026

SAFETY DATA SHEET

Page 3

EXPOSURE CONTROLS:

VENTILATION/ ENGINEERING MEASURES ...	Provide adequate ventilation sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust or fumes, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
RESPIRATORY PROTECTION	If airborne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air.
SKIN PROTECTION	Wear adequate protective gloves/ clothing impervious to the material.
EYE/ FACE PROTECTION	Wear eye/ face protection. Safety goggles with side shields are recommended.
OTHER PROTECTIVE EQUIPMENT	An eyewash station and safety shower should be available in the immediate working area. Other equipment may be required depending on each workplace.
GENERAL HYGIENE CONSIDERATIONS	Do not eat, drink or smoke while working with this product. Do not breathe dust or mist. Avoid contact with eyes, skin and clothing. Upon completion of work or prior to work breaks, wash hands thorough. Remove and wash contaminated clothing before re-use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE	Solid, granular
COLOUR	Light grey
ODOUR	None
pH LEVEL	Not available
MELTING/ FREEZING POINT	Not available
BOILING POINT	Not available
FLASH POINT	Not applicable
FLAMMABILITY	Not applicable
VAPOUR PRESSURE	Not available
RELATIVE VAPOUR DENSITY (Air=1) (mg/m3)	Not available
SPECIFIC GRAVITY @ 20°C (68°F)	2.2 grams/mL
VISCOSITY	Not available
KINEMATIC VISCOSITY	No data available
VOC's (Volatile Organic Compounds)	0 grams/L
SOLUBILITY IN WATER (%W/W)	Insoluble
PARTICLE CHARACTERISTICS	No data available

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY	Non-reactive material.
CHEMICAL STABILITY	The product is chemically stable.
HAZARDOUS REACTIONS	Hazardous polymerization does not occur.
CONDITIONS TO AVOID	Avoid high humidity or wet conditions.
INCOMPATIBLE MATERIALS	No information available.
HAZARDOUS DECOMPOSITION PRODUCTS	None.

SECTION 11: TOXICOLOGICAL INFORMATION

ACUTE TOXICITY	Not classified based on available information.
MUTAGENICITY	Not expected to be mutagenic.
CARCINOGENICITY	Crystalline Silica is classified by IARC as 2A-possibly carcinogenic to humans.
REPRODUCTIVE EFFECTS	Not classified based on available information.
SENSITIZATION TO MATERIAL	Skin sensitization: Not classified based on available information. Respiratory sensitization: Not classified based on available information.
SPECIFIC TARGET ORGAN EFFECTS	Repeated Exposure: Causes damage to organs (Lungs) through prolonged or repeated exposure. Prolonged exposure can cause silicosis.
MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE	Pre-existing asthma.
SYNERGISTIC MATERIALS	None known.
TOXICOLOGICAL DATA	There is no data available for this product.

SDS-27
Revised July 9th, 2026

SAFETY DATA SHEET		Page 4
SECTION 12: ECOLOGICAL INFORMATION		
ECOTOXICITY	No data is available for the product itself. Do not empty into drains.	
PERSISTANCE AND DEGRADABILITY	No data is available.	
BIOACCUMULATION POTENTIAL	No data is available.	
MOBILITY IN SOIL	No data is available.	
OTHER ADVERSE ENVIRONMENTAL EFFECTS	No adverse environmental effects.	
SECTION 13: DISPOSAL CONSIDERATIONS		
HANDLING FOR DISPOSAL	No special requirements. Handle in accordance with good industrial hygiene and safety practice.	
METHODS OF DISPOSAL	Dispose of as normal garbage or in accordance with all applicable federal, state, provincial and local regulations.	
SECTION 14: TRANSPORTATION INFORMATION		
TDG CLASSIFICATION	Not regulated.	
SECTION 15: REGULATORY INFORMATION		
TSCA INFORMATION	All ingredients listed in the composition of this product are either listed on the TSCA inventory or are in compliance with a TSCA inventory exemption.	
CEPA INFORMATION	All ingredients listed appear on the Domestic Substances List (DSL)	
WHMIS CLASSIFICATION	Class D-Division 2, Subdivision A	
CPR (CANADA) COMPLIANCE	Meets all requirements	
SECTION 16: OTHER INFORMATION		
ACGIH	American Confederation of Governmental Industrial Hygienists	
AIHA	American Industrial Hygiene Association	
CAS	Chemical Abstract Services	
CEPA	Canadian Environmental Protection Act	
CFR	Code of Federal Regulations	
DOT	Department of Transportation	
IARC.....	International Agency for Research on Cancer	
IATA	International Air Transport Association	
NIOSH	National Institute of Occupational Safety and Health	
NTP.....	National Toxicology Program	
PEL	Permissible Exposure Limit	
STEL	Short Term Exposure Limit	
TWA	Time-Weighted Average	
TSCA	Toxic Substances Control Act	
OSHA	Occupational Safety and Health Administration	
PREPARED BY:	Camelia Gardo	
TELEPHONE NUMBER:	(905) 669-5013	
PREPARATION DATE:	July 9 th , 2026	
The above information pertains to this product as currently formulated and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.		